

NITROGEN GENERATOR

MODEL - PNF-3000, PNF-3000A



- Suitable for: Car, Light Truck
- Pump the air from the tyre by the internal vacuum generator
- Auto-Start Inflation
- Single Tyre Application
- 72PSI / 5bar / 500kPa
- Generates nitrogen from your compressed air
- 2 Pre-Filters
- 50L internal nitrogen storage tank
- Remain at last setting
- Audible and visual end of the cycle signal indicators
- LED display
- 1 No. 10m standard hose with single clip-on open tyre chuck

TECHNICAL SPECIFICATIONS

Compressed Air Input Range	87-145PSI/6-10bar /600-1000kPa
Compressed Air Input Flow	500L/min(17.0cfm)
Operating Temperature Range	-20 /-4°F to 70 / 158°F
N2 Purity	95~99+%
Nitrogen Output	58L/min(2.0cfm)@116PSI/8bar/800kPa
Maximum Nitrogen Pressure in Tank	102PSI / 7bar / 700kPa
Power Requirement Voltage	AC220V 50Hz 1 Phase
Power Consumption	30VA
Dimensions HxWxD	1255x700x435 mm
Net Weight	87 kg

* Specifications subject to change without notice

PRECISION TESTING MACHINES PVT. LTD.

HEAD OFFICE: S-12, Okhla Industrial Area, Phase - II, New Delhi - 110 020 (India)

Tel.: 011-4161-0000 (4 lines), 2638-6612 Fax: 011-26383790

E-mail : sales@precisionworld.net / service@precisionworld.net / www.precisionworld.net