

Semi Automatic Tyre Changer with Swing Arm

MODEL - PTC-1036



- Semi Automatic Tyre Changer with swing arm, reliable and at the right price.
- Horizontal tool positioning by means of threaded hand wheel, single action level.
- Self-centering four jaw chuck and powerful bead breaker.
- The machine adopts the parkerising bead breaker cylinder having bead breaking power 2500Kg to bead break the tyre from rim easily.
- The control pedal assembly has the step-move function which can stop the clamp at any position to clamp the rim conveniently.
- The machine equips the protective cover for clamps and mounting head as standard configuration to avoid damaging the rim.
- The clamp is made of special material, strong and durable
- Angle of mount/dismount tool can be adjusted and calibrated.
- Rim size 10"-22"

HIGHLIGHTS



Strong and durable made of special steel




Universal switch with 40A silvered contacts which are more robust and better life span

TECHNICAL SPECIFICATIONS

Max. wheel diameter	1000 mm
Rim diameter	10" - 22"
Maximum Wheel width	3" - 13"
Rim Clamping from outside	10" - 20"
Rim Clamping from inside	12" - 22"
Electric motor	0.75Kw / 1.1 Kw
Mains supply	I Ph. 220 V / 3 Ph. 380 V
Operating air pressure	8-12 bar
Dimensions LxWxH	780 x 995 x 1730 mm
Net Weight	192.5 kg

DIMENSIONS



* Specifications subject to change without notice

PRECISION TESTING MACHINES PVT. LTD.

HEAD OFFICE: S-12, Okhla Industrial Area, Phase - II, New Delhi - 110 020 (India)

Tel.: 011-4161-0000 (4 lines), 2638-6612 Fax: 011-26383790

E-mail : sales@precisionworld.net / service@precisionworld.net / www.precisionworld.net